

4x4 TRUCK PULL

Saturday, September 07, 2024 at 7:00pm

Hot Stock Diesel Rules

1. **WEIGHT:**
Maximum weight of 8,500 lbs.
No weight brackets or hanging weights allowed in front of vehicles.
Weights must be in the bed of the truck only and securely fastened or contained safely therein. No weights permitted inside the cab. No weights allowed under hood or in the wheel wells. No weights may be suspended under the body/chassis or behind panels/parts.
2. Four-wheel hydraulic brakes are mandatory.
3. The engine must be a stock-appearing compression ignition engine from a one-ton or smaller pickup truck. Swaps between manufacturers are not permitted. Ford must have a Powerstroke engine, Dodge must have a Cummins engine, Chevrolet/GMC must have a Duramax engine, etc.
4. No aftermarket cylinder heads.
5. Exhaust must exit behind the cab. Stacks exiting through the hood or fender well are prohibited.
6. Water injection is prohibited. All system components must be removed from the truck.
7. DOT street legal tires are required. No studded tires, tire chains or any tire not specifically intended for street use are permitted.
8. Traction bars and devices are permitted; they must be bolt-on only; welds are permitted for attachment to frame or axle housing.
9. The rear suspension must maintain a minimum compression shock travel of two inches; compression stops must be adjustable.
10. The fuel must be pump #1/#2 diesel only. Soy/Bio Diesel fuel is permitted. NITROUS OXIDE is prohibited along with other oxygen extenders as well as the use of PROPANE is also prohibited. All system components MUST be removed from the truck. Fuel tanks must be OEM and in the factory location. Fuel cells are permitted as long as they are not located in the drivers compartment.
11. All Headlights must be in OEM location and functional.
12. A rear bumper or "Reese" style hitch is the only acceptable type of hitch. No other types of hitches are permitted.
13. Maximum hitch height of 26"-4wd, or 30"-2wd. To be measured at the point of hook. Opening minimum of 3 inches wide (side to side) and 3.75" inches long (front to back)
14. The use of hand-throttle controls is prohibited.
15. No exposed Duals.
16. Passengers are not permitted at any time either in the pits or on the track.
17. Complete headlight and tail-light assemblies (all) are mandatory and must be in place and operative.

For complete Rules & Regulations see www.oxhillfair.org.