

**4x4 TRUCK PULL**  
**Wednesday, September 04, 2024 at 7:00pm**  
Registration begins at 5:30pm  
**4 Classes**

- **\$20.00 ALL Track Gate Entry, includes Pits**
- All persons ENTERING the TRACK GATE must sign a release form and receive an armband.
- **Hook Fee for driver: \$0.00**
- An index card will be provided upon arrival on fairgrounds. Please fill out the index card and bring to the Registration Stand, **after** you have weighed in. Bring **BOTH** index cards to the Registration Stand to register.
- All classes require a minimum of 5 Trucks.
- Officials may run any combination of classes.
- **No Riders permitted.**
- **Paying Back 3 places.**
- **Purse: \$900**
- **For complete Rules & Regulations see [www.oxhillfair.org](http://www.oxhillfair.org).**
- Running order will be determined the day of the pull.
- Pulling Sled by: "Destination Unknown"

# **4x4 TRUCK PULL**

**Wednesday, September 04, 2024 at 7:00pm**

## **4. 4,500lb. Modified 4x4 Trucks**

1. Maximum weight of 4,500 lbs.
2. Maximum wheelbase of 135 inches. Must have been a factory 4x4. Maximum width of 102" permitted.
3. Tires:  
D.O.T 33/14.5 or metric equivalent.  
29/11 dirt track tires are permitted.  
No recaps or bar tires permitted, sipping and sanding of tires is permitted for the purpose of resurfacing only. Cleaning up existing tire grooves allowed. Rear tires can be offset inward to center of front tires, no duals. Tire tracks must half lap. Use of dirt deflectors is prohibited.
4. Ballast: Additional weight is permitted, no weights allowed inside the cab. Front weights and brackets may not extend further than 60 inches from the center of the front axle.
5. Batteries must be securely mounted, may be in the stock location, in the bed, or mounted on the front weight rack/box.
6. Maximum hitch height of 24 inches. The Hitch plate is to be a minimum of 1/2 inch thick at any point. Minimum hitch length is 27% of truck overall wheelbase no shorter than 24". Measurement taken from center of axle tube to hook point. Hitch pivot or attachment point cannot be any further forward than the center of the rear axle.
7. Any engine brand may be used with any brand of body/frame. Rear of the engine block can be no further forward than the center of the front axle, and the engine must be behind the factory grill location.
8. Small block engines only, maximum of 360 cubic inches. (No LS or HEMI type blocks permitted)
9. Any heads are allowed but must be OEM valve angle. (No LS or Hemi style heads permitted)
10. Aluminum cast intake is allowed - NO tunnel rams, NO sheet metal intakes
11. All exhaust systems must discharge vertically or downward. (Vertically is defined as being within 10 degrees any direction of being plumb or downward style must discharge straight back.) No rain caps permitted.
12. Gasoline or racing fuel is permitted, no alcohol permitted. Nitrous oxide and all other oxygen extenders are PROHIBITED.
13. All trucks must be equipped with a kill switch .

For complete Rules & Regulations see [www.oxhillfair.org](http://www.oxhillfair.org).