

# 4x4 TRUCK PULL

## Open Street Gas & Diesel Combined

### Gasoline 4x4 Trucks

1. Maximum weight 6,500 pounds.
2. No hanging weight or weight bars are permitted.
3. Hidden weights are permitted, but must be securely fastened and not visible.
4. All trucks must be licensed, registered and pass state inspection. NO dealer plates permitted.
5. All truck bodies and interior must be OEM. No racing seats or hand throttles are permitted.
6. Factory beds or manufactured flat beds are permitted. Lightening of the truck frame is not permitted. No tube chassis permitted.
7. All engines must be OEM. Aluminum heads are permitted. Engines must be in factory location. Radiator must be OEM and factory size.
8. All vehicles must run unaltered D.O.T. approved tires with the D.O.T. stamp visible.
9. Real Wheels are permitted.
10. Maximum of a 24" hitch height. Must utilize a "Reece" style hitch. Hitch must be mounted within 6" of the frame. Opening minimum of 3.5" x 3.75".

### Diesel 4x4 Trucks

1. Weight: 8,700 pounds
2. No hanging or front mounted weight permitted. Any hidden weight must be securely fastened.
3. All trucks must be licensed, registered and pass state inspection. NO dealer plates permitted.
4. All truck bodies and interior must be OEM. No racing seats or hand throttles are permitted.
5. Factory beds or manufactured flat beds are permitted. Factory side shields or fenders are mandatory.
6. Diesel fuel is the only fuel permitted.
7. All vehicles must run unaltered D.O.T. approved tires with the D.O.T. stamp visible.
8. Real Wheels are permitted.
9. Hood stacks are only permitted IF the truck is inspected and insured.
10. Maximum of a 22" hitch height. Must utilize a "Reece" style hitch. Hitch must be mounted within 6" of the frame. Opening minimum of 3.5" x 3.75".