

## High Output Gas Big Block Trucks

1. Maximum weight is set at 6200 pounds.
2. Additional added weight is permitted.
3. Hanging weights and brackets may not extend more than 195 inches from the centerline of the rear axle. Weights may not extend more than 60" from the centerline of the front axle.
4. Weights may be securely fastened inside the engine compartment, or in the bed, but not inside the cab.
5. Weights may be securely fastened inside the engine compartment, or in the bed, but not inside the cab.
6. Truck exterior must be stock in appearance. Full fiberglass bodies are not permitted. OEM cab must have O.E.M. firewall and O.E.M. floor for safety. Bed floor is not required however there must be a tonneau cover.
7. Any single, four-barrel carburetor permitted. No dual carburetors permitted. NO Tunnel Rams or Sheet Metal intakes are permitted.
8. Rear of the engine block must remain at least 12" behind the centerline of the front axle.
9. Open headers allowed. All vehicles must have upward-pointing exhaust of the truck hood or under the fender-downward. Exhaust may be routed vertically up through the vehicle hood. The exhaust must be minimum 6" higher than the hood when the hood is in the closed position.
10. No cubic inch limit is imposed.
11. Aluminum cylinder heads are allowed without restriction.
12. Suspension may be either blocked or solid, with no hydraulic suspension or air bags permitted. Traction control devices are NOT permitted. Front working brakes are required.
13. Suspension must have a minimum of 2" of travel.
14. Drivetrain size must not exceed 1 ton. Only OEM frame rails are permitted. Wheelbase may not exceed 136".
15. Transfer cases must be 1 ton or less. No drop boxes are permitted.
16. Gasoline, E-85 (ethanol), alcohol, and racing fuel are permitted. Nitrous oxide and all other oxygen extenders are PROHIBITED. Fuel tanks may be mounted on the front of the weight box.

17. All tires must be DOT approved, maximum size of 35x12.50. (Metric conversion of this tire size is 315/70 or 315/75). No cut, altered, or sharpened tires are permitted. No duals allowed. Use of dirt deflectors is prohibited.

18. Maximum hitch height of 26 inches. The opening in the hitch must be 3.75" x 3.0". The length of the hitch measured from the center of the rear axle to the hitch point may be no shorter than 27% of the actual wheelbase of the truck. No part of the hitch can extend more than 3" above the frame rail or further forward than the centerline of the rear axle.

19. Trucks in this class do not have to be licensed or inspected or insured. If not street legal, must have all safety equipment in place. Any street licensed truck that chooses to enter this class must be fully licensed and insured.

20. All drivers must wear a minimum of shirt, long pants, and closed toed shoes during competition.

Driver's window must be completely rolled up while competing. Drivers must wear a seatbelt or shoulder harness when hooked to the sled. Passengers are not permitted at any time either in the pits or on the track