SHOWROOM GAS 4x4 TRUCK PULL RULES & REGULATIONS

- 1. Showroom Gas Small Block 412 C.I. & less 6500lb.
- 2. Showroom Gas Big Block 413 C.I. & up to 6800 lb.
- 3. Two add-ons or modifications are allowed. Add on being aluminum intake headers Holley carburetor
- 4. Rough idle will be considered a modification.
- 5. Vehicle should sound and look like an everyday driver. Must run on pump gas.
- 6. Inspection and license necessary, owner's card and insurance card may be asked for to verify legality of vehicle.
- 7. D.O.T. tires only tread can be no deeper than original tread.
- 8. Must pull off of bumper or Reese hitch hitch point must be rear most part of vehicle.
- 9. Hitch point can be no higher than frame.
- 10. No heavy front bumpers or hang weights. Snow plow rigging allowed.
- 11. Weights can be put in bed none in cab. Must be secured. Weights that fall off will result in a DQ.
- 12. No weights under hood. This will be checked before, during and after class is pulled.
- 13. POSI-traction carriers allowed. No welded carriers or spools permitted in front rear.
- 14. Compression ratio should be no higher than year of truck being pulled.
- 15. 10-inch-wide rim allowed. 12-inch tread width.
- 16. A fully functional front and rear suspension is required.
- 17. Suspension must have a minimum of 2-inches of travel.
- 18. Traction bars or Clamp suspension allowed.