

WILD STREET DIESEL 4x4 TRUCK PULL RULES & REGULATIONS

Maximum weight of 8,700lb.

All trucks must be licensed, registered, and pass state inspection.

Dealer plates are *NOT* permitted.

1. WEIGHT:
 - No hanging or front-mounted weight.
 - Hidden weight must be securely fastened.
 - Stock-appearing bumpers are permitted.
2. WHEELS & TIRES:
 - Must run unaltered, D.O.T. approved tires with visible D.O.T. stamp.
 - No “Real Wheels” are permitted.
 - Factory duals are permitted.
 - May not exceed 35X12.50 or metric equivalent if running duals.
 - Any tire size is permitted if running single wheels.
3. AIR:
 - No intake in any non-OEM locations such as headlights.
4. FUEL:
 - Diesel Fuel is the only permitted fuel.
5. INJECTABLES:
 - Anyone using nitrous or any other injectable will be required to have a full fire suit, including gloves and full-face helmet.
 - All nitrous bottles must be permanently mounted.
 - Thermostatically controlled heating by a commercially available, blanket-type warmer is permitted.
6. INTERIOR:
 - Full interior must be OEM.
 - Hand throttles are *NOT* permitted.
7. ENGINE:
 - Engine must be a factory option in a manufactured 1-ton truck.
 - Engine mounts must be factory and in the factory location.
 - Radiator must be factory size and in OEM location.
 - Radiator must be functional.
 - All cooling for the truck must be located in the factory locations.
8. DRIVELINE & SUSPENSION:
 - Must utilize an OEM driveline.
 - If the truck is towed to the event, drive shaft loops are mandatory.
 - All 4-wheel brakes must work.
 - If the truck is jacked up, all four wheels will stop when the brake is applied.
 - Suspension must remain factory.
 - Suspension can be blocked.
9. FRAME:
 - No frame lightening is permitted.
 - Cutting or altering the frame to reduce weight is not permitted.
 - Tube chassis are not permitted.
 - Vehicle must utilize the factory frame.
10. BED:
 - Factory beds or manufactured flat beds are permitted.
 - Factory bed floors are mandatory.
 - Must be able to support 250lb in any part of the bed.

- All flatbeds must extend to the outermost part of the outside of the tire.
- Factory inner fenders or side shields are mandatory.

11. HITCH:

- Maximum of a 22-inch hitch height.
- Must utilize a REESE style hitch.
- Hitch must hit first if backed against a wall.
- Must be mounted within six (6) inches of the frame.
- Opening minimum of 3.5" X 3.75" inches.
- Twist-style clevises are not permitted.
- There are no turbo limitations.